

## #1 in appliance parts

## Parts & Accessories

REFRIGERATION

	REFRIGERATION
OVERLOADS, RELAYS & KLIXONS	RELAYS ELECTROMAGNETIC RELAYS - 220V
4387489 DEFROST THERMOSTAT   ORIGINAL PART SUITABLE FOR USE ON MOST   EARLY MODEL WHIRLPOOL SIDE-BY-SIDE REFRIGERATORS	REL3 - 1/3HP REL4 - 1/4HP REL5 - 1/5HP REL6 - 1/6HP REL8 - 1/8HP
	RELAYS ELECTROMAGNETIC RELAYS - 220V RELS-8 - 1/8HP
OVERLOAD KLIXON     SUITABLE WITH 1/20HP - 1/3HP       COMPRESSORS       ROP3 - 1/3HP       ROP4 - 1/4HP       ROP5 - 1/5HP       ROP6 - 1/6HP       ROP8 - 1/8HP	RELS-20 - 1/20HP
ROP20 - 1/20HP	RIC20 SOLID STATE PUSH-ON RELAY - 220V
OVERLOAD KLIXONSOLID STATE RELAYROP4SS - 1/4HP ROP5SS - 1/5HP ROP6SS - 1/6HP ROP8SS - 1/8HPImage: Constant of the second	SUITABLE WITH COMPRESSORS - 1/12 HP THRU 1/2HP - INCLUDES TERMINALS
AGESEBYY -B ACHW	RIC21 SOLID STATE RELAY - 220V
RDT70   DEFROST STAT +12 TO -5 degC     WITH FUSE +70degC     SUITABLE FOR USE ON SAMSUNG     AND KIC FROST-FREE     REFRIGERATORS	UNIVERSAL
	RIC23 RELAY/OVERLOAD COMBINATION KIT - 220V
RDT75 DEFROST TERMINATOR - 75degC   SUITABLE FOR USE ON KIC 3A   FROST-FREE MODELS Image: Constraint of the second sec	SUITABLE WITH COMPRESSORS - 1/3HP AND 1/4HP
	RIC25 RELAY/OVERLOAD COMBINATION KIT - 220V
REL10 NECCHI MINI ES5   RELAY/OVERLOAD UNIT   SUITABLE WITH NECCHI 1/6HP   COMPRESSORS	SUITABLE WITH COMPRESSORS - 1/5HP, 1/6HP, AND 1/8HP

## Parts & Accessories

UITABLE WITH COMF /5HP AND 1/6HP	PRESSORS -		
		SUITABLE WITH 1/3HP COMPRESSORS	
RIC26	110V COIL RELAY CONTACT	FOR ROP4	
OMPLETE WITH 8 PIN	N BASE	SUITABLE WITH 1/4HP COMPRESSORS	
RIC32	SOLID STATE PUSH ON REL	AY - ROP5	
UITABLE WITH COMF /12HP THRU 1/2HP	PRESSORS	SUITABLE WITH 1/5HP COMPRESSORS	
RIC33	SOLID STATE PUSH ON REL	AY - ROP6	OVERLOAD KLIXON
UITABLE WITH COMF /5HP AND 1/6HP	PRESSORS -	SUITABLE WITH 1/6HP COMPRESSORS	
RML55	CLIP-ON DEFROST THERMOS	STAT ROP8	OVERLOAD KLIXON
ORMALLY OPEN OPENS @ 13DEGC, DEGC	CLOSES @	SUITABLE WITH 1/8HP COMPRESSORS	
ROP20	OVERLOAD KLIXON	<b>RTHF</b> OEM REF: 7500 0017 0	THERMIC FUSE
UITABLE WITH 1/20H OMPRESSORS	P	SUITABLE FOR USE ON FROST-FREE MODELS	